



TECHNICAL DATA SHEET

2.7 PAINT STRIPPERS AND PAINT REMOVERS



► Quitacqua

Paint stripper

1155 / Version 3 / 05-03-2025



DESCRIPTION

Special stripper for removing plastic, textured and streaked paints.

PROPERTIES

- Liquid product for removing plastic, textured, scratched effect paints, etc.
- Does not contain any acid or alkaline products.
- Toxicity free, it does not cause skin burns.
- Interior and exterior application.

USES

Especially suitable for stripping plastic, textured, streaked paints, etc. even though they have been applied for a long time to substrates such as plaster, cement, wood and metal. . Because of its special thixotropy, it does not drip.

TECHNICAL DATA

Appearance	Liquid gel.
Colour	Transparent.
Density at 20°C (Kg/L)	1 ± 0.05.
Yield (m²/L):	2-6.
Working time (min)	30, with a waiting time of 60 being more favourable.
Maximum working time (hours)	4.
Cleaning of utensils and stains	With water before drying.
Volatile Organic Compounds (COV).	Maximum product content 0,100 g/l,

HOW TO APPLY

- Stir the product until totally smooth.

SURFACE AND AMBIENT CONDITIONS

AMBIENT TEMPERATURE:

Do not paint at a temperature of below 7°C .

RELATIVE HUMIDITY:

Never apply with relative humidity exceeding 80%.

AMBIENT CONDITIONS:

It is not recommended to paint in rainy weather or at times of peak heat.

POSSIBLE APPLICATION SYSTEMS

Use a brush or roller for normal application of Quitacqua. Apply thick films of the product using a brush, leaving it to act for an appropriate waiting time, taking into account that the longer it is left, the easier and deeper the stripping of the paint will be. The attacked and dissolved mass is then removed using a spatula. If it is a very hard or old paint it is best to score it, making criss-cross cuts, before application and repeat this operation several times because the product will slowly attack and dissolve the layer or layers of paint.

SAFETY

Consult the current safety data sheet for safe handling (Section 8.2). Unsuitable for children. Keep out of the reach of children. Do not place painted surfaces into the mouth.



2.7 PAINT STRIPPERS AND PAINT REMOVERS

► Quitacqua

Paint stripper

1155 / Version 3 / 05-03-2025

REMOVAL

Take the necessary measures to ensure waste is kept to an absolute minimum. Analyse all possible methods for reuse or recycling, in line with the local and national legislation in force. Take the necessary measures to ensure waste is kept to an absolute minimum. Analyse all possible methods for reuse or recycling. Do not pour down drains or into the environment. Dispose of the product at an authorised waste disposal site or through an authorised waste management company. Waste must be handled, stored and disposed of pursuant to current local- national legislation.

STORAGE

See storage conditions indicated in section 7.2 of the current safety data sheet. Store the containers away from high temperatures, direct exposure to the sun and frost. Maximum recommended storage time: 12 months from manufacture in fully sealed original container, indoors and at temperatures between 5° and 35° C.

LEGAL TEXT NOTE

This information and, in particular, the recommendations regarding the application and final use of the product, are given in good faith, based on the current knowledge and experience of Isaval Paints of the products when they are properly stored, handled and applied, in normal situations, within its useful life, according to the recommendations of Pinturas Isaval. In practice, the possible differences in the materials, supports and actual conditions at the place of application are such that it cannot be inferred from the information in this document, no any other written recommendation, neither any advice offered, will insure the guarantee in terms of marketing or suitability for particular purposes, neither any obligation outside of any legal relationship that may exist. The user of the products must carry out the tests to verify their suitability according to the use they want to give. Pinturas Isaval reserves the right to change the specifications of its products. The property rights of third parties must be respected. All orders are accepted according to the terms of our current General Conditions of Sale and Supply. Users should know and use the latest and updated version of the local Product Data Sheets, a copy of which will be sent to whoever requests them, or can also be obtained on the page www.isaval.es. All data in this document are based on laboratory tests conducted at 20°C and 1 atm pressure. Measurements taken "on-site" may vary due to circumstances beyond our control, such as changes in environmental conditions of pressure and temperature.