#### TECHNICAL DATA SHEET







#### ▶ Patina gel

Patina wax

1373 / Version 2 / 04-09-2023

\*





## **DESCRIPTION**

Patina wax is used to make the coloured finish on the reliefs of ANTIQUE WALLS.

#### **PROPERTIES**

- It is very easy to use and gives high quality finishes.
- Odourless and non-toxic.
- · Ready-to-use.

#### USES

Odourless gel ready for application with a sponge or cloth. Provides a silky and strong finish.

#### **TECHNICAL DATA**

Finish	Silky.
Colour	Wall colour charts.
Density at 20°C (Kg/L)	1.1 ± 0.05
Yield (L/m2)	0.08 - 0.1 L/m2, depending on required structure
Drying time (20°C).	1 h
Volatile Organic Compounds (COV).	Maximum product content 10,30 g/l

#### **HOW TO APPLY**

• Stir the product until totally smooth.

#### POSSIBLE APPLICATION SYSTEMS

Patina gel is used neat on "Antique walls" or plastic paint. Lightly soak a sponge or cloth in it and rub it gently along the finishing reliefs of "ANTIQUE WALLS". Take care not to overload with too much product so as not to leave residue that can leave stains on the finish.

### **FINISH GEL PÁTINA:**

- Yield: 0.08 0.1 L/m2
- Coats: 2

#### SAFETY

Consult the current safety data sheet for safe handling (Section 8.2). Unsuitable for children. Keep out of the reach of children. Do not place painted surfaces into the mouth.

#### **REMOVAL**

Take the necessary measures to ensure waste is kept to an absolute minimum. Analyse all possible methods for reuse or recycling, in line with the local and national legislation in force. Take the necessary measures to ensure waste is kept to an absolute minimum. Analyse all possible methods for reuse or recycling. Do not pour down drains or into the environment. Dispose of the product at an authorised waste disposal site or through an authorised waste management company. Waste must be handled, stored and disposed of pursuant to current local- national legislation.

### **STORAGE**

See storage conditions indicated in section 7.2 of the current safety data sheet. Store the containers away from high temperatures, direct exposure to the sun and frost. Maximum recommended storage time: 12 months from manufacture in fully sealed original container, indoors and at temperatures between 5° and 35° C.



# TECHNICAL DATA SHEET





#### ▶ Patina gel

Patina wax

1373 / Version 2 / 04-09-2023

#### **LEGAL TEXT NOTE**

This information and, in particular, the recommendations regarding the application and final use of the product, are given in good faith, based on the current knowledge and experience of Isaval Paints of the products when they are properly stored, handled and applied, in normal situations, within its useful life, according to the recommendations of Pinturas Isaval. In practice, the possible differences in the materials, supports and actual conditions at the place of application are such that it cannot be inferred from the information in this document, no any other written recommendation, neither any advice offered, will insure the guarantee in terms of marketing or suitability for particular purposes, neither any obligation outside of any legal relationship that may exist. The user of the products must carry out the tests to verify their suitability according to the use they want to give. Pinturas Isaval reserves the right to change the specifications of its products. The property rights of third parties must be respected. All orders are accepted according to the terms of our current General Conditions of Sale and Supply. Users should know and use the latest and updated version of the local Product Data Sheets, a copy of which will be sent to whoever requests them, or can also be obtained on the page "www.Isaval.es". Data on this Sheet are based on laboratory tests. The measures taken "on site" may vary due to circumstances beyond our control.

