



TECHNICAL DATA SHEET

7. HIGH-END DECORATION

► Antique walls

Plastering rustic walls

1376 / Version 1 / 05-03-2025



DESCRIPTION

Plaster prepared in paste for interior decoration and making reliefs for simulating rustic and antique walls.

PROPERTIES

- Ready-to-use.
- The surface to which it is applied does not need to be flat.
- Very easy and smooth to use.
- Has high adhesion and cohesion.

USES

This product is used in high-end decoration to obtain the reliefs and unevenness that appeared in antique walls. For walls of entrance areas and domestic or commercial accommodation rooms. Then finish off with a colour patina (PATINA GEL).

TECHNICAL DATA

Appearance	Rustic.
Colour	Neutral base.
Density at 20°C (Kg/L)	1.7 ± 0.05
Usage	0.6 - 1.4 kg/m ² , depending on required structure
Touch dry	24 h
Cleaning of utensils and stains	With water.
Volatile Organic Compounds (COV).	Maximum product content 0,00 g/l

HOW TO APPLY

- Stir the product until totally smooth.
- The surfaces to be painted must be clean, dry and free of dust, grease, saltpetre, etc.

SURFACE AND AMBIENT CONDITIONS

AMBIENT TEMPERATURE:

Apply at temperatures higher than 10°C.

SURFACE PREPARATION

UNPAINTED SURFACES:

New unpainted surfaces:

- Remove efflorescences, product residues and foreign substances (grease, dust, oils and/or derivatives, etc.).

7. HIGH-END DECORATION

► Antique walls

Plastering rustic walls

1376 / Version 1 / 05-03-2025

POSSIBLE APPLICATION SYSTEMS

Antique walls can be applied with a plastic trowel. An uneven layer is applied to achieve a relief effect and the required structure. After 24 hours, remove the sharp edges left behind by sanding gently and clean away the dust that has formed. Coloured PATINA GEL is applied using a sponge or muslin cloth, taking care not to leave any residue. This operation is carried out by gently rubbing the sponge along the tips of the relief.

PRIMERS:

- Fixenol Pigmented: non-homogeneous surfaces (various materials, areas with different colours, repairs, etc.), where FIXENOL PIGMENTED is to be applied in the desired colour, in order to regularise the colour, absorption and appearance of the surface. Yield: 8 - 15 m²/L. Coats: 1

FINISH MUROS A LA ANTIGUA:

- Yield: 0,6 - 1, 4 kg/m²
- Coats: 2

SAFETY

Consult the current safety data sheet for safe handling (Section 8.2). Unsuitable for children. Keep out of the reach of children. Do not place painted surfaces into the mouth.

REMOVAL

Take the necessary measures to ensure waste is kept to an absolute minimum. Analyse all possible methods for reuse or recycling, in line with the local and national legislation in force. Take the necessary measures to ensure waste is kept to an absolute minimum. Analyse all possible methods for reuse or recycling. Do not pour down drains or into the environment. Dispose of the product at an authorised waste disposal site or through an authorised waste management company. Waste must be handled, stored and disposed of pursuant to current local- national legislation.

STORAGE

See storage conditions indicated in section 7.2 of the current safety data sheet. Store the containers away from high temperatures, direct exposure to the sun and frost. Maximum recommended storage time: 12 months from manufacture in fully sealed original container, indoors and at temperatures between 5° and 35° C.

LEGAL TEXT NOTE

This information and, in particular, the recommendations regarding the application and final use of the product, are given in good faith, based on the current knowledge and experience of Isaval Paints of the products when they are properly stored, handled and applied, in normal situations, within its useful life, according to the recommendations of Pinturas Isaval. In practice, the possible differences in the materials, supports and actual conditions at the place of application are such that it cannot be inferred from the information in this document, no any other written recommendation, neither any advice offered, will insure the guarantee in terms of marketing or suitability for particular purposes, neither any obligation outside of any legal relationship that may exist. The user of the products must carry out the tests to verify their suitability according to the use they want to give. Pinturas Isaval reserves the right to change the specifications of its products. The property rights of third parties must be respected. All orders are accepted according to the terms of our current General Conditions of Sale and Supply. Users should know and use the latest and updated version of the local Product Data Sheets, a copy of which will be sent to whoever requests them, or can also be obtained on the page www.isaval.es. All data in this document are based on laboratory tests conducted at 20°C and 1 atm pressure. Measurements taken "on-site" may vary due to circumstances beyond our control, such as changes in environmental conditions of pressure and temperature.