



TECHNICAL DATA SHEET

2.6 STAIN AND ANTI-HUMIDITY TREATMENT



► Cotiz

Non-chalk effect varnish

1557 / Version 3 / 04-03-2025



DESCRIPTION

Mono-component acrylic matt varnish for protection and treatment of chalk effect on walls.

PROPERTIES

- High physical and chemical resistance.
- Resistance to household cleaning products.
- High transparency.
- Flexible.
- Good adhesion and levelling.
- Odourless.
- Quick drying.
- Interior and exterior application.
- Ready-to-use.

USES

Protection and decoration of walls, improving resistance to chalk effect.

TECHNICAL DATA

Appearance	Matt.
Viscosity (Brookfield RVT at 20°C). Poises	18-22.
Density at 20°C (Kg/L)	1 ± 0.05.
Volatile Organic Compounds (COV).	Maximum product content 0,90 g/l,
Yield (m²/L):	14-17.
Drying at 20°C (min)	30.
Second coat (hours)	2-3.
% maximum dilution	Do not dilute, apply to the use.
Cleaning of utensils and stains	With water before drying.

HOW TO APPLY

- Stir the product until totally smooth.
- The surfaces to be painted must be clean, dry and free of dust, grease, saltpetre, etc.
- If the surface is already painted, ensure the previous paint is in good condition and well-adhered.

SURFACE AND AMBIENT CONDITIONS

AMBIENT TEMPERATURE:

Do not paint at a temperature of below 10°C.

RELATIVE HUMIDITY:

Never apply with relative humidity exceeding 80%.

AMBIENT CONDITIONS:

It is not recommended to paint in rainy weather or at times of peak heat.



2.6 STAIN AND ANTI- HUMIDITY TREATMENT

► Cotiz

Non-chalk effect varnish

1557 / Version 3 / 04-03-2025

SURFACE PREPARATION

PRE-PAINTED SURFACES IN POOR CONDITION:

Pre-painted surface in poor condition:

- Remove efflorescences, product residues and foreign substances (grease, dust, oils and/or derivatives, etc.).
- Remove dirt from the tiles with a brush and then remove any residue generated. Clean the tiles with soap and water to remove any existing particles that might affect the anchoring of the finish. Paint using the normal procedure.
- If the surface is in poor condition or flaking, poorly adhered residues must be removed using chemical or mechanical stripping
- Clear oil or grease residue.

POSSIBLE APPLICATION SYSTEMS

Use a sponge roller or spray gun for normal application of Cotiz anti-chalk effect. For spray application use fine nozzles, minimum 1.5-2, with high pressure, from 2.5 to 4 atmospheres.

FINISH COTIZ EFECTO ANTITIZA:

- Yield: 14-17 m²/L
- Coats: 1-2

SAFETY

Consult the current safety data sheet for safe handling (Section 8.2). Unsuitable for children. Keep out of the reach of children. Do not place painted surfaces into the mouth.

REMOVAL

Take the necessary measures to ensure waste is kept to an absolute minimum. Analyse all possible methods for reuse or recycling, in line with the local and national legislation in force. Take the necessary measures to ensure waste is kept to an absolute minimum. Analyse all possible methods for reuse or recycling. Do not pour down drains or into the environment. Dispose of the product at an authorised waste disposal site or through an authorised waste management company. Waste must be handled, stored and disposed of pursuant to current local- national legislation.

STORAGE

See storage conditions indicated in section 7.2 of the current safety data sheet. Store the containers away from high temperatures, direct exposure to the sun and frost. Maximum recommended storage time: 12 months from manufacture in fully sealed original container, indoors and at temperatures between 5° and 35° C.

LEGAL TEXT NOTE

This information and, in particular, the recommendations regarding the application and final use of the product, are given in good faith, based on the current knowledge and experience of Isaval Paints of the products when they are properly stored, handled and applied, in normal situations, within its useful life, according to the recommendations of Pinturas Isaval. In practice, the possible differences in the materials, supports and actual conditions at the place of application are such that it cannot be inferred from the information in this document, no any other written recommendation, neither any advice offered, will insure the guarantee in terms of marketing or suitability for particular purposes, neither any obligation outside of any legal relationship that may exist. The user of the products must carry out the tests to verify their suitability according to the use they want to give. Pinturas Isaval reserves the right to change the specifications of its products. The property rights of third parties must be respected. All orders are accepted according to the terms of our current General Conditions of Sale and Supply. Users should know and use the latest and updated version of the local Product Data Sheets, a copy of which will be sent to whoever requests them, or can also be obtained on the page www.isaval.es. All data in this document are based on laboratory tests conducted at 20°C and 1 atm pressure. Measurements taken "on-site" may vary due to circumstances beyond our control, such as changes in environmental conditions of pressure and temperature.