



## TECHNICAL DATA SHEET

### 5.1 OPEN PORE WOOD STAIN

#### ► Xanol Teak oil

Restoration oil

1905 / Version 5 / 05-03-2025



## DESCRIPTION

Oil especially indicated for restoring furniture and all types of wood.

## PROPERTIES

- Protects, embellishes and enhances the grain of the wood.
- Excellent resistance in interior and exterior applications, washable, barely leaves a layer, does not flake.
- Repels water, oil and food stains.
- Interior and exterior application.

## USES

Furniture, chairs, decks and all kinds of wooden elements in general.

## TECHNICAL DATA

<b>Finish</b>	Glossy.
<b>Colour</b>	Transparent, Teak and Honey.
<b>Density at 20°C (Kg/L)</b>	0.88 ± 0.05
<b>Yield (m<sup>2</sup>/L):</b>	6 - 7
<b>Drying at 20°C (hours)</b>	2
<b>Second coat (hours)</b>	12 - 24

## HOW TO APPLY

- The surfaces to be painted must be clean, dry and free of dust, grease, saltpetre, etc.

## POSSIBLE APPLICATION SYSTEMS

Apply Xanol teak oil with a paintbrush or varnishing wad, applying an even and well spread layer. It can also be applied to new wood by applying 3 or 4 layers by paintbrush, leaving each layer to dry for between 12 and 24 hours.

### FINISH XANOL ACEITE DE TECA:

- Yield: 6 - 7 m<sup>2</sup>/l
- Coats: 2

## SAFETY

Consult the current safety data sheet for safe handling (Section 8.2). Unsuitable for children. Keep out of the reach of children. Do not place painted surfaces into the mouth.

## REMOVAL

Take the necessary measures to ensure waste is kept to an absolute minimum. Analyse all possible methods for reuse or recycling, in line with the local and national legislation in force. Take the necessary measures to ensure waste is kept to an absolute minimum. Analyse all possible methods for reuse or recycling. Do not pour down drains or into the environment. Dispose of the product at an authorised waste disposal site or through an authorised waste management company. Waste must be handled, stored and disposed of pursuant to current local- national legislation.

## STORAGE

See storage conditions indicated in section 7.2 of the current safety data sheet. Store the containers away from high temperatures, direct exposure to the sun and frost. Maximum recommended storage time: 24 months from manufacture in fully sealed original container, indoors and at temperatures between 5° and 35° C.

## 5.1 OPEN PORE WOOD STAIN

### ► Xanol Teak oil

Restoration oil

1905 / Version 5 / 05-03-2025

## LEGAL TEXT NOTE

This information and, in particular, the recommendations regarding the application and final use of the product, are given in good faith, based on the current knowledge and experience of Isaval Paints of the products when they are properly stored, handled and applied, in normal situations, within its useful life, according to the recommendations of Pinturas Isaval. In practice, the possible differences in the materials, supports and actual conditions at the place of application are such that it cannot be inferred from the information in this document, no any other written recommendation, neither any advice offered, will insure the guarantee in terms of marketing or suitability for particular purposes, neither any obligation outside of any legal relationship that may exist. The user of the products must carry out the tests to verify their suitability according to the use they want to give. Pinturas Isaval reserves the right to change the specifications of its products. The property rights of third parties must be respected. All orders are accepted according to the terms of our current General Conditions of Sale and Supply. Users should know and use the latest and updated version of the local Product Data Sheets, a copy of which will be sent to whoever requests them, or can also be obtained on the page [www.isaval.es](http://www.isaval.es). All data in this document are based on laboratory tests conducted at 20°C and 1 atm pressure. Measurements taken "on-site" may vary due to circumstances beyond our control, such as changes in environmental conditions of pressure and temperature.