



TECHNICAL DATA SHEET

5.4 SPECIFIC USES

► Xanol Wood cleaner

Wood stain cleaner

1906 / Version 2 / 05-12-2023



DESCRIPTION

Powerful cleaner for woods stained or creped by external agents such as rain, pollution, UV rays, etc.

PROPERTIES

- Removes traces of dirt, mould and grease that stain wood.
- Makes the wood look clean and new.

USES

Indicated for restoring wood before applying any type of wood stain, varnish or oil.

TECHNICAL DATA

Appearance	Liquid.
Colour	Transparent.
Density at 20°C (Kg/L)	1.03 ± 0.05
Maximum dilution	1 (cleaner): 5 (water). Dilute gradually depending on how dirty the wood is
Touch dry (hours)	48

HOW TO APPLY

- Stir the product until totally smooth.
- Apply to small surfaces by area so that it does not dry out and cause the dirt to stick to the wood again.
- Brush the wood with the cleaner to remove most of the dirt and rinse with water.

POSSIBLE APPLICATION SYSTEMS

After applying Xanol wood cleaner, leave it to act for 5 minutes. Brush regularly with a plastic or hard natural bristle brush. Remove dirt as you work and rinse with clean water to remove any traces of dirt and detergent. Allow to dry for several days until there is no moisture left on the wood. If there are any traces of dirt left, repeat the operation.

SAFETY

Consult the current safety data sheet for safe handling (Section 8.2). Unsuitable for children. Keep out of the reach of children. Do not place painted surfaces into the mouth.

REMOVAL

Take the necessary measures to ensure waste is kept to an absolute minimum. Analyse all possible methods for reuse or recycling, in line with the local and national legislation in force. Take the necessary measures to ensure waste is kept to an absolute minimum. Analyse all possible methods for reuse or recycling. Do not pour down drains or into the environment. Dispose of the product at an authorised waste disposal site or through an authorised waste management company. Waste must be handled, stored and disposed of pursuant to current local- national legislation.

STORAGE

See storage conditions indicated in section 7.2 of the current safety data sheet. Store the containers away from high temperatures, direct exposure to the sun and frost. Maximum recommended storage time: 24 months from manufacture in fully sealed original container, indoors and at temperatures between 5° and 35° C.



5.4 SPECIFIC USES

► Xanol Wood cleaner

Wood stain cleaner

1906 / Version 2 / 05-12-2023

LEGAL TEXT NOTE

This information and, in particular, the recommendations regarding the application and final use of the product, are given in good faith, based on the current knowledge and experience of Isaval Paints of the products when they are properly stored, handled and applied, in normal situations, within its useful life, according to the recommendations of Pinturas Isaval. In practice, the possible differences in the materials, supports and actual conditions at the place of application are such that it cannot be inferred from the information in this document, no any other written recommendation, neither any advice offered, will insure the guarantee in terms of marketing or suitability for particular purposes, neither any obligation outside of any legal relationship that may exist. The user of the products must carry out the tests to verify their suitability according to the use they want to give. Pinturas Isaval reserves the right to change the specifications of its products. The property rights of third parties must be respected. All orders are accepted according to the terms of our current General Conditions of Sale and Supply. Users should know and use the latest and updated version of the local Product Data Sheets, a copy of which will be sent to whoever requests them, or can also be obtained on the page "www.Isaval.es". Data on this Sheet are based on laboratory tests. The measures taken "on site" may vary due to circumstances beyond our control.