



TECHNICAL DATA SHEET

2.7 PAINT STRIPPERS AND PAINT REMOVERS



► Xanol Stripping gel

Wood stripping gel

1916 / Version 5 / 05-03-2025



DESCRIPTION

Stripper for removal of most paints. Exclusively.

PROPERTIES

- Liquid product for removing plastic, textured, scratched effect paints, etc.
- Does not contain any acid or alkaline products.
- It does not contain acid or alkaline products and therefore respects the painted surface, not causing corrosion to metal alteration in the colour of wood.
- Because of its special thixotropy, it does not drip.

USES

Especially indicated for stripping most types of paints: varnishes, pigmented and transparent nitrocellulose, pigmented and transparent polyurethane lacquers, synthetic enamels, plastic paints, chlorinated rubber paints, etc.; applied to surfaces such as plaster, cement, wood and metal.

TECHNICAL DATA

Appearance	Liquid.
Colour	Transparent.
Density at 20°C (Kg/L)	1.16 ± 0.05
Working time (min)	5 - 10
Yield (m ² /L):	3 - 6

HOW TO APPLY

- If it is a very hard or old paint it is best to score it, making criss-cross cuts, before application and repeat this operation several times because the product will slowly attack and dissolve the layer or layers of paint.
- Before repainting on the stripped surface, it must be fully cleaned using the appropriate solvent in each case or soapy water, if feasible.

POSSIBLE APPLICATION SYSTEMS

Use a brush, roller or spatula for normal application of Xanol stripper or paint remover. Never apply using a spray gun. The product should not be left for more than one hour on the surface to be stripped because it will form a hard layer.

FINISH XANOL GEL DECAPANTE:

- Yield: 3 - 6 m²/L
- Coats: 1

SAFETY

Consult the current safety data sheet for safe handling (Section 8.2). Unsuitable for children. Keep out of the reach of children. Do not place painted surfaces into the mouth.

REMOVAL

Take the necessary measures to ensure waste is kept to an absolute minimum. Analyse all possible methods for reuse or recycling, in line with the local and national legislation in force. Take the necessary measures to ensure waste is kept to an absolute minimum. Analyse all possible methods for reuse or recycling. Do not pour down drains or into the environment. Dispose of the product at an authorised waste disposal site or through an authorised waste management company. Waste must be handled, stored and disposed of pursuant to current local- national legislation.

STORAGE

See storage conditions indicated in section 7.2 of the current safety data sheet. Store the containers away from high temperatures, direct exposure to the sun and frost. Maximum recommended storage time: 24 months from manufacture in fully sealed original container, indoors and at temperatures between 5° and 35° C.



2.7 PAINT STRIPPERS AND PAINT REMOVERS

► **Xanol Stripping gel**

Wood stripping gel

1916 / Version 5 / 05-03-2025

LEGAL TEXT NOTE

This information and, in particular, the recommendations regarding the application and final use of the product, are given in good faith, based on the current knowledge and experience of Isaval Paints of the products when they are properly stored, handled and applied, in normal situations, within its useful life, according to the recommendations of Pinturas Isaval. In practice, the possible differences in the materials, supports and actual conditions at the place of application are such that it cannot be inferred from the information in this document, no any other written recommendation, neither any advice offered, will insure the guarantee in terms of marketing or suitability for particular purposes, neither any obligation outside of any legal relationship that may exist. The user of the products must carry out the tests to verify their suitability according to the use they want to give. Pinturas Isaval reserves the right to change the specifications of its products. The property rights of third parties must be respected. All orders are accepted according to the terms of our current General Conditions of Sale and Supply. Users should know and use the latest and updated version of the local Product Data Sheets, a copy of which will be sent to whoever requests them, or can also be obtained on the page www.isaval.es. All data in this document are based on laboratory tests conducted at 20°C and 1 atm pressure. Measurements taken "on-site" may vary due to circumstances beyond our control, such as changes in environmental conditions of pressure and temperature.