



## TECHNICAL DATA SHEET

### 9.4 SPECIFIC USES

#### ► Sanit Aditivo

Preservative additive

2642 / Version 1 / 05-03-2025



## DESCRIPTION

Additive for the protection of the dry film of any type of water-based paint against the appearance of mold and algae, in humid environments or that favor their proliferation.

## PROPERTIES

- Protection against a wide range of molds and algae.
- Prevents the fixation of mold on the paint film in environments conducive to its proliferation.
- Compatible with most known aqueous systems.

## USES

Dry film protective additive for paints, coatings, stuccos, wood lasurs and other industrial applications, against degradation caused by molds and algae. Suitable for water-based systems.

## TECHNICAL DATA

<b>Appearance</b>	Milky white
<b>pH</b>	6 - 7
<b>Density at 20°C (Kg/L)</b>	1,1
<b>Viscosity (Brookfield RVT at 20°C). Poises</b>	20 - 60

## HOW TO APPLY

- The surfaces to be treated with paint to which the product has been added must be cleaned and disinfected prior to painting them.
- For professional use only
- Add SANIT ADITIVO to the paint and stir the mixture until it is suitably dispersed. It is very important for this operation to be carried out correctly.

## POSSIBLE APPLICATION SYSTEMS

The product is marketed in two formats:

- 140 ml container for facade coatings, size 15 liters.
- 40 ml container for Facade Coatings size 4 liters or Interior Plastics size 15 liters.

For any other situation, it is recommended to consult the technical department.

## SAFETY

Consult the current safety data sheet for safe handling (Section 8.2). Unsuitable for children. Keep out of the reach of children. Do not place painted surfaces into the mouth.

## REMOVAL

Take the necessary measures to ensure waste is kept to an absolute minimum. Analyse all possible methods for reuse or recycling, in line with the local and national legislation in force. Take the necessary measures to ensure waste is kept to an absolute minimum. Analyse all possible methods for reuse or recycling. Do not pour down drains or into the environment. Dispose of the product at an authorised waste disposal site or through an authorised waste management company. Waste must be handled, stored and disposed of pursuant to current local- national legislation.

## STORAGE

See storage conditions indicated in section 7.2 of the current safety data sheet. Store the containers away from high temperatures, direct exposure to the sun and frost. Maximum recommended storage time: 12 months from manufacture in fully sealed original container, indoors and at temperatures between 5° and 35° C.



## 9.4 SPECIFIC USES

### ► Sanit Aditivo

Preservative additive

2642 / Version 1 / 05-03-2025

## LEGAL TEXT NOTE

This information and, in particular, the recommendations regarding the application and final use of the product, are given in good faith, based on the current knowledge and experience of Isaval Paints of the products when they are properly stored, handled and applied, in normal situations, within its useful life, according to the recommendations of Pinturas Isaval. In practice, the possible differences in the materials, supports and actual conditions at the place of application are such that it cannot be inferred from the information in this document, no any other written recommendation, neither any advice offered, will insure the guarantee in terms of marketing or suitability for particular purposes, neither any obligation outside of any legal relationship that may exist. The user of the products must carry out the tests to verify their suitability according to the use they want to give. Pinturas Isaval reserves the right to change the specifications of its products. The property rights of third parties must be respected. All orders are accepted according to the terms of our current General Conditions of Sale and Supply. Users should know and use the latest and updated version of the local Product Data Sheets, a copy of which will be sent to whoever requests them, or can also be obtained on the page [www.isaval.es](http://www.isaval.es). All data in this document are based on laboratory tests conducted at 20°C and 1 atm pressure. Measurements taken "on-site" may vary due to circumstances beyond our control, such as changes in environmental conditions of pressure and temperature.